



## Get the look of wood, with the durability of metal.

## • Beyond Innovation

We went back to the drawing board – we started with a blank sheet of paper with the goal of addressing 3 key features that other lookalikes have miss ed.

Improved Moisture Management

New profile behind the plank to increase rain screen functionality

Better Material Optimization Improved strength to weight ratio

Timeless Look / Precision Install

Classic profile design that allows for increased installation precision within 0.5mm (20 thou) for reduced risk of compression resulting from material expansion and contraction across the width of the plank



Our system comes in 6 wood grains. Custom color matching also available.

AAMA 2604 - coating finish standard





AL13<sub>®</sub> is made of solid noncombustible aluminum extrusions. CAN/ULC-S114

ASTM E136 , see passed

CAN/ULC-S102 **I \* I** flame spread (0) - smoke development (0)

ASTM E84 Flame spread (0) - smoke development (0)

Wind + Water



AL13<sup>®</sup> Planks are cut-to-fit on site, secured using system clips and system frame components - allowing for on-the-fly changes. AL13<sup>®</sup> system clips and extrusions work together to create a secure system with built-in moisture management.

AAMA 508 - pressure equalized rainscreen

ASTM E330 - windload Intertek evaluated for Canadian NBC part 9 & Part 5 CCMC equivalency

## Contact

www.al13.com info@al13.com +1 855 438 2513 All Product Orders orders@al13.com





No additional off-site fabrication required. Panels are cut to fit on site and secured using a patented process, saving time and money.

Wind + Water



AL13 $_{\odot}$  Panels are cut-to-fit on site and secured using the system frame components - allowing for on-the-fly changes. AL13 $_{\odot}$  system clips and extrusions work together to create a secure system with built-in moisture management.

AAMA 508 - pressure equalized rainscreen

ASTM E330 - windload



AL13 $_{\odot}$  Panels are available in standard polyethylene (PE) or Class A2 fire rated (FR) core - the highest quality fire resistant panels on the market

CAN/ULC-S102 FR Core: flame spread (0) - smoke development (5) ASTM E84 FR Core: flame spread (0) - smoke development (30)

CAN/ULC-S134 FR core only

NFPA 285 FR core only



The AL13<sup>®</sup> Panel System is available in 9 standard solid, 5 wood grains and 4 metallic finishes - custom color matching also available.

AAMA 2605 - coating finish standard



Patented

4

Years of R&D has allowed AL13<sup>®</sup> to create an innovative system solution to on-site installation and lead time constraints inherent with other products





www.al13.com info@al13.com +1 855 438 2513 All Product Orders orders@al13.com